

# J&B东莞市骏佳电子科技有限公司

## 产品规格书

### 1. SCOPE[ 适用范围]

This specification covers the PCS product series.

本规范适用于PCS系列产品

### 2. Part name & part number 【部件名称 & 部件编号】

Part name [ 部件名称 ]	Part number[ 部件编号 ]
1. 27 PIN HEADER	PCS

### 3. RATINGS[ 标准额定值]

Item[ 项目 ]	Standard[ 规格 ]	
Rated voltage[ 额定电压 ]	250V	AC/DC
Rated current[ 额定电流 ]	1A	
Operating temperature[ 使用温度范围 ]	- 40°C To + 105°C	

### 4. TEST CONDITION[ 测试条件]

The test and measurement , unless otherwise specified, shall be carryout at a temparature of 15 tp 35°C, Relative humidity of 25 to 85% , and atmospheris pressure of 86 to 106kPa. However, when any doubt arises on the judgment value under it , the test and measurement shall be carryout at a temperature of 20±2°C, relative humidity of 60 to 70% , and atmospheric pressure of 86 to 106kPa

[除非特别说明之外，一般测试及测量将于温度15~35°C，相对湿度25~85%，大气压力86~106kPa之条件下完成，但若于上述条件下有任何影响判定值的疑虑，可考虑在温度20±2°C，相对湿度60~70%及大气压力86~106kPa之条件下完成试验。]

### 5. Appearance[ 外观]

By looking , there shall not be any abnormality such as deformity , exfoliation of plating , etc , which can reduce performance. No defect shuch as cracks scratches or blemishes . [经目视观察，外观不可有变形，电镀脱落等会降低其功能的异常现象，也不可有严重破裂、刮伤或污损之缺点。]

### 6. ELECTRICAL EFFICIENCY[ 电气特性]

NO. [ 编号 ]	Item[ 项目 ]	Test Method[ 试验方法 ]	Requirement[ 性能要求 ]
6. 1	Contact Resistance [ 接触电阻 ]	EIA-364-23C Subject mated contacts assembled in housing to closed circuit current of 100 mA maximum at open circuit at 20 mV maximum. 在开路电压最大为20mV的状态下，对组装好的端子进行最大电流为100mA的回路测试。	1. Initial value : 20 mΩ max. 初始值 最大20 mΩ 2. Final value : 30 mΩ max. 结束值 最大30 mΩ
6. 2	Insulation Resistance [ 绝缘电阻 ]	EIA-364-21C Mate connectors, apply 500V DC for 1 minute between adjacent terminal or ground. [ 在插合连接器相邻接触件之间施加500V DC 电压持续1分钟 ]	1000MΩ Min.

NO. [ 编号 ]	Item [ 项目 ]	Test Method [ 试验方法 ]	Requirement [ 性能要求 ]
6. 3	Withstanding Voltage [ 耐电压 ]	EIA-364-20 Test again after wire up 2 mins, Mate connectors, apply 500V AC Between adjacent terminal or ground. [ 在各相邻接触件间施加500V ]	No insulation breakdown [ 塑胶无爆裂 ]

## 7. ENVIRONMENTAL EFFICIENCY [ 环境特性 ]

NO. [ 编号 ]	Item [ 项目 ]	Test Method [ 试验方法 ]	Requirement [ 性能要求 ]
7. 1	Heat Resistance [ 耐热试验 ]	EIA-364-17 Mated connector shall be placed in an environmental for 96 hours at +85±2°C. [ 将插合的连接器放在温度为 +85±2°C 的环境中96小时 ]	1. No evidence of damage 无损坏 2. The electrical performances meet the spec. specified in paragraph 6. 1 电气性能符合表格6. 1要求。
7. 2	Cold Resistance [ 耐冷试验 ]	EIA-364-59C mated connector shall be placed in an environmental for 48 hours at -25±3°C. [ 将插合的连接器放在温度为 -25±3°C 的环境中48小时 ]	1. No evidence of damage 无损坏 2. The electrical performances meet the spec. specified in paragraph 6. 1 电气性能符合表格6. 1要求。
7. 3	Humidity [ 耐湿性试验 ]	EIA-364-31 Mate connectors, 40±2°C in temperature and 90~95%RH in an environmental for 96 hours. After testing connector shall be left alone for 1 to 2 hours in a room ambient. [ 将插合的连接器，温度40±2°C，相对湿度90~96%的环境中，持续96小时。试验后，连接器须于室温中放置1~2小时，再测定 ]	1. No evidence of damage 无损坏 2. The electrical performances meet the spec. specified in paragraph 6 电气性能符合表格 6 要求。
7. 4	Temperature Cycling [ 温度循环 ]	EIA-364-30 low temerature: -40±3°C high tempetature: 105±3°C After 5 cycles at the normal environment for testing after 2 hours [ 低温: -40°C±3°C ] [ 高温: 105°C±3°C ] [ 5此循环后放置在正常环境中恢复2小时后进行测试 ]	1. No evidence of damage 无损坏 2. The electrical performances meet the spec. specified in paragraph 6. 1 电气性能符合表格6. 1要求。
7. 5	Salt spray [ 盐雾测试 ]	EIA-364-26 Salt concentration: 5% / Temperature: 35±2°C Testing time: 8 hours, After salt is removed by running water and a drop is removed, it is measured. [ 盐水比重: 5% / 温度35±2°C ] [ 试验时间: 8小时, 试验结束后用清水将残留盐份清洗并将水滴清楚后, 才可测量 ]	1. No evidence of damage 无损坏 2. The electrical performances meet the spec. specified in paragraph 6. 1 电气性能符合表格6. 1要求。

NO. [ 编号 ]	Item [ 项目 ]	Test Method [ 试验方法 ]	Requirement [ 性能要求 ]
7. 6	Solderability [ 可焊性测试 ]	EIA-364-52 Soldering Time, 3~5 S Solder Temperature, 245±5 °C [ 焊锡时间: 3~5秒 ] [ 焊锡温度: 245±5°C ]	95% min. of solder area [ 焊锡面积 ≥ 95% ]
7. 7	Resistance to soldering heat [ 耐焊性 ]	EIA-364-71 Soldering Time, 5~10 S Solder Temperature, 260±5 °C [ 焊锡时间: 5~10秒 ] [ 焊锡温度: 260±5°C ]	Without deformation of case or excessive loosen. [ 塑胶不可有明显的变形或损坏 ]

#### 8. MECHANICAL EFFICIENCY [ 机械特性 ]

NO. [ 编号 ]	Item [ 项目 ]	Test Method [ 试验方法 ]	Requirement [ 性能要求 ]
8. 1	Terminal retention Force [ 端子保持力 ]	EIA-364-29 Fix the dynamometer 150mm away from the wire of the connection, then apply axial pull out force at a speed ≤ 10N/S on the terminal assembled in the housing. [ 将测力器固定在距离150mm处，在连接器轴方向施加拉力，施力速度 ≤ 10N/S，将端子从孔位中拉出 ]	2.5 N Min. Only per terminal [ 单一端子 ]